

Compact Interior

UK Stock Range

Decor	Finish	Name	NCS	Ral	LRV	Length	Width	Thickness
0606	FH	Artic White	S 0502-R50B	9003	0.8	4100	1850	12mm
0085	FH	White	S 0502 - G50Y	9010	0.85	2800	1850	12mm
0851	FH	Winter White	S 0505-Y30R	9001	0.82	2800	1850	12mm
0280	FH	Safari	S1010-Y40R	1015	0.66	2800	1850	12mm
0074	FH	Pastel Grey	S 2500 - N	7038	0.5	2800	1850	12mm
0075	FH	Dark Grey	S 5000-N	7037	0.24	2800	1850	12mm
0077	FH	Charcoal	S 7005 - R50B	7015	0.13	2800	1850	12mm
0080	FH	Black	S 9000-N	9004	0.05	2800	1850	12mm
0619	FH	May Green	3050 - G20Y	6018	0.28	2800	1850	12mm
0630	FH	Sea Green	S 2010 - B70G	6019	0.55	2800	1850	12mm
0274	FH	Pistachio	2010 - G50Y	-	0.56	2800	1850	12mm
0718	FH	Artic	S1030 - R90B	-	0.55	2800	1850	12mm
0237	FH	Gentian Blue	S 5040-R80B	5010	0.1	2800	1850	12mm
0717	FH	Atlantic	S 2060 - R90B	5015	0.22	2800	1850	12mm
0095	FH	Papaya	S0560 - Y40R	-	0.49	2800	1850	12mm
0210	FH	Intensive Red	S 0580-Y90R	3020	0.2	2800	1850	12mm
0212	FH	Sun Yellow	S 1070 - Y10R	1023	0.54	2800	1850	12mm
0558	FH	White Punto			0.74	2800	1850	12mm
0559	FH	Pastel Grey Punto			0.43	2800	1850	12mm
3361	FH	Dove Blue Punto			0.41	2800	1850	12mm
0328	FH	Brushed Aluminium			0.42	2800	1850	12mm
0102	FH	Maple			0.67	2800	1850	12mm
0291	FH	Beech 2			0.37	2800	1850	12mm
0544	FH	Austrian Walnut			0.15	2800	1850	12mm
0867	FH	Light Elm Montezuma			0.27	2800	1850	12mm
0905	FH	Cheyenne Walnut			0.18	2800	1850	12mm



Environmentally Friendly Production

The Kraft paper and decorative layers are impregnated with resins on impregnation lines, dried and then pressed at high pressure and temperatures, producing a durable moisture resistant panel. The exhaust air extracted from the drying process is treated by regenerative thermal oxidation in which heat produced thereby is redirected back into the process.

For installing this efficient air handling facility FunderMax were given the best practice the "climate:active" award by the Austrian Energy Agency, and the Federal Ministry for the Environment.

The production plant can thus reduce its emissions by approximately 10,000 tons of CO2 per year.

Corporate Mission Statement

FunderMax is to become and remain the best company in the industry. - We focus our activities on those products and services with which we can be among the best and enthuse our customers - We build long-term partnerships with customers, employees, vendors and society...

Sheet Sizes:

- GR = 2800 x 1300 mm
- JU = 4100 x 1300 mm
- TK = 2140 x 1060 mm*
- SP = 2800 x 1850 mm*
- XL = 4100 x 1850 mm*

* Limited decor range, please refer to our interior collection.

Max Compact panels are high pressure laminates (HPL) manufactured to standard EN 438 4 type CGS for demanding applications: (e.g. Washroom cubicles, office furniture, wall cladding, wet rooms, lockers etc).

DECORMAX

www.fundermax.at

UK Compact Interior Range



for
people
who
create

interior

UK Compact Interior range



0606FH



0085FH



0851FH




0280FH




0074FH



0075FH



0077FH



0080FH




0619FH



0630FH



0274FH



0718FH



0237FH



0717FH



0095FH



0210FH




0212FH



558FH



559FH



3361FH



0328FH



0102FH



0291FH



0544FH



0867FH



0905FH



FUNDERMAX

Compact Interior

UK Stock Range

The UK stock range consists of 26 decors which are carried in sheet size 2800 x 1850 x 12mm.

* Please note some decors are available in 4100 x 1850 x 12mm.

QUALITIES:

Standard: type CGS as per EN 438-4.

Core: black, standard quality.

F-Core (FR): Available upon request.

Max Compact Laminates are produced to order. Max Compact Laminates are also available with Dualis overlays for creating unique designs. Please refer to our interior collection.

Thickness tolerances:

- 2,0 – 2,9 mm ± 0,2 mm
- 3,0 – 4,9 mm ± 0,3 mm
- 5,0 – 7,9 mm ± 0,4 mm
- 8,0 – 11,9 mm ± 0,5 mm
- 12,0 – 15,9 mm ± 0,6 mm
- 16,0 – 20,0 mm ± 0,7 mm

FSC certified products are available upon request. Full details of all accreditation to be found via the website www.fundermax.at.

Technical Information

Recommendations and procedural information for the correct fitting and handling of Compact Grade Laminate can be found via the website www.fundermax.at.



Standard Grade:

- 2140 x 1060 x 1.0mm*
- 2800 x 1300 x 1.0mm

Postforming Grade:

- 4100 x 1300 x 0.8mm

* Limited decor range, please refer to our stock programme.

FunderMax are also able to offer matching Star Favorit Melamine Faced Chipboard in both standard grade and moisture resistant grade to match the UK range, minimum quantities will apply, Star Favorit MFC is produced to order.

Formats:

- 2820 x 2070 mm = 5.84 m²
- 2800 x 1850 mm = 5.18 m² (surface finish HG only).

Thickness:

- 12 mm, 16 mm, 19 mm, 22 mm, 25 mm, 28 mm (32 mm and 38 mm on request).